



## Complete Lighting Source

STANDARD FINISHES: (add as suffix)

- BA Black Powder Paint
- BH White Powder Paint
- BM Bronze Powder Paint
- BV Dark Green Powder Paint
- 01 Satin

\* Other finishes available, consult factory

Mtg Hgt	Wall Thick.	Butt Dia.	Top Dia.	Base Dia.	Bolt Circle	Bolt Project	Net Weight	Lum Weight	Anchor Bolts	Arm Length	Maximum EPA			
											80	90	100	110
30	.188	5	0	11	10 - 12	3.375	376	25x EPA	1 x 36 x 4		11.7	7.9	5.1	2.9

NOTES: (1) Effective Projected Area (EPA) in square feet. EPAs calculated using wind velocity (mph) indicated plus 30% gust factor.  
(2) Standard Finish - Satin Ground.

MOUNTING: (specify)

2.375" tenon

3.0" tenon

4.0" tenon

For side mounting: specify luminaire quantity and orientation.

Luminaire drilling must be supplied at time of order.

SHAFT:

Pole shaft shall be constructed of seamless extruded tube of 6063 aluminum alloy per ASTM B221 and shall be full-length heat treated after welding on the base flange to T-6 temper. Shaft shall be free of longitudinal welds. Pole shaft cap, when required, shall be of cast aluminum of 443 or 356F aluminum alloy and attached utilizing stainless steel screws.